

**INDUSTRIAL COMPONENT DATA****603048 LEGRAND ICP-M 3P 5A**

Brand: LEGRAND | Manufacturer Part Number: 603048



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | LEGRAND                         |
| MPN / Reference | 603048                          |
| Catalog number  | 603048                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-02148C6864                   |
| Generated       | 2026-08-01                      |

**Product Overview**

ICP-M 3P 5A

ICP-M Switch - control of power 3 P - 400 V~ - 5 To - 3 mód.

ICP-M - Power control switch 3 P - 400V~ - 5A - 3mod

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **LEGRAND > TERTIARY CIRCUIT BREAKERS****Additional Product Information**

Product features

Wattage control switch (ICP-M three-pole 400 V~ - Curve ICP-M - rated current: 5 - Number of modules: 3 General characteristics

Switch power control to 50A curve ICP-M - circuit Breakers residual current protection - Curve ICP-M according to UNE 20317 - Power of court to 6000A according to UNE 20317 - Use: Switch for Power Control of the subscriber captive Screws Portaetiquetas incorporated

ETIM for 603048 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Concurrently switching neutral conductor (EF005997)

No  
Voltage type (EF000187)  
AC  
Rated short-circuit breaking capacity  $I_{cn}$  according to EN 60898 at 400 V (EF009555)  
6 kA  
Additional equipment possible (EF008148)  
Yes  
Rated impulse withstand voltage  $U_{imp}$  (EF011980)  
4 kV  
Number of protected poles (EF005548)  
3  
Frequency (EF000416)  
50 Hz  
Built-in depth (EF000218)  
44 mm  
Number of poles (total) (EF008618)  
3  
Pollution degree (EF002570)  
2  
Width in number of modular spacings (EF002950)  
53.4  
Rated insulation voltage  $U_i$  (EF001366)  
500 V  
Over voltage category (EF002569)  
3  
Rated current (EF000227)  
5 A  
Current limiting class (EF002568)  
3  
Flush-mounted installation (EF007517)  
Yes  
Release characteristic (EF000889)  
Other  
Rated voltage (EF000228)  
400 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 603048 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.