

INDUSTRIAL COMPONENT DATA

603053 LEGRAND ICP-M 3P 25A

Brand: LEGRAND | Manufacturer Part Number: 603053



Manufacturer	LEGRAND
MPN / Reference	603053
Catalog number	603053
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-CC935F936D
Generated	2026-07-31

Product Overview

ICP-M 3P 25A

ICP-M Switch - control of power 3 P - 400 V~ - 25 A - 3 mód.

ICP-M - Power control switch 3 P - 400V~ - 25A - 3mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Product features

Wattage control switch (ICP-M three-pole 400 V~ - Curve ICP-M - rated current: 25a - Number of modules: 3 General characteristics

Switch power control to 50A curve ICP-M - circuit Breakers residual current protection - Curve ICP-M according to UNE 20317 - Power of court to 6000A according to UNE 20317 - Use: Switch for Power Control of the subscriber captive Screws Portaetiquetas incorporated

ETIM for 603053 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Concurrently switching neutral conductor (EF005997)

No
Voltage type (EF000187)
AC
Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V (EF009555)
6 kA
Additional equipment possible (EF008148)
Yes
Rated impulse withstand voltage U_{imp} (EF011980)
4 kV
Number of protected poles (EF005548)
3
Frequency (EF000416)
50 Hz
Built-in depth (EF000218)
44 mm
Number of poles (total) (EF008618)
3
Pollution degree (EF002570)
2
Width in number of modular spacings (EF002950)
53.4
Rated insulation voltage U_i (EF001366)
500 V
Over voltage category (EF002569)
3
Rated current (EF000227)
25 A
Current limiting class (EF002568)
3
Flush-mounted installation (EF007517)
Yes
Release characteristic (EF000889)
Other
Rated voltage (EF000228)
400 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 603053 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.