

INDUSTRIAL COMPONENT DATA

603082 LEGRAND ICP-M 4P 20A

Brand: LEGRAND | Manufacturer Part Number: 603082



Manufacturer	LEGRAND
MPN / Reference	603082
Catalog number	603082
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-735BCD9CB1
Generated	2026-07-29

Product Overview

ICP-M 4P 20A

ICP-M - Switch power control 4 P - 400 V~ - 20 A - 4 mód.

ICP-M - Power control switch 4 P - 400V~ - 20A - 4mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > TERTIARY CIRCUIT BREAKERS

Additional Product Information

Product features

Wattage control switch (ICP-M Tetrapolar 400 V~ - Curve ICP-M - rated current: 20 - Number of modules: 4 General characteristics

Switch power control to 50A curve ICP-M - circuit Breakers residual current protection - Curve ICP-M according to UNE 20317 - Power of court to 6000A according to UNE 20317 - Use: Switch for Power Control of the subscriber captive Screws Portaetiquetas incorporated

ETIM for 603082 Circuit breakers and fuses (EC000042)

Feature Name

Feature Value

Explosion-proof (EF004663)

No

Degree of protection (IP) (EF005474)

IP20

Concurrently switching neutral conductor (EF005997)

Yes

Voltage type (EF000187)

AC

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V (EF009555)

6 kA

Additional equipment possible (EF008148)

Yes

Rated impulse withstand voltage U_{imp} (EF011980)

4 kV

Number of protected poles (EF005548)

4

Frequency (EF000416)

50 Hz

Built-in depth (EF000218)

44 mm

Number of poles (total) (EF008618)

4

Pollution degree (EF002570)

2

Width in number of modular spacings (EF002950)

71.2

Rated insulation voltage U_i (EF001366)

500 V

Over voltage category (EF002569)

3

Rated current (EF000227)

20 A

Current limiting class (EF002568)

3

Flush-mounted installation (EF007517)

Yes

Release characteristic (EF000889)

Other

Rated voltage (EF000228)

400 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 603082 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.