

INDUSTRIAL COMPONENT DATA

644107 LEGRAND 10 C14-C13 LOCK 1M RG CABLES

Brand: LEGRAND | Manufacturer Part Number: 644107



Manufacturer	LEGRAND
MPN / Reference	644107
Catalog number	644107
Category	Power cord
Minimum order	1 Pcs
Document ID	EO-D5CA8CBE2A
Generated	2026-08-02

Product Overview

10 C14-C13 LOCK 1M RG CABLES

Set of 10 C14-C13 1m power cables with red plug lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path
LEGRAND > VARIOUS VDI

Additional Product Information

Power cables used to connect active equipment (servers) to a PDU. The unique C13 plug swivel mechanism, which fits any standard C14 input, prevents accidental disconnection from the server.

Connection 1 Other

Cable entry connection 1 Straight

Connection 2 Other

Cable entry connection 2 Straight

System of connectors connected to the system No

Number of threads 3

Nominal Conductor Section 1 mm²

Longitude 3 /

Cover material Polyvinyl chloride (PVC)

Temperature resistance -20-70 °C

Nominal intensity 10 A

Nominal Voltage 250-250 V

Outer Cover Color Red

Coiled cable No

With cable switch No
Outer diameter approx. 7 mm
Reaction class to fire according to EN 13501-6 none
Reaction to fire according to EN 13501-6: Smoke production none
Reaction to fire according to EN 13501-6: Flammable drops/particles none
Reaction to fire according to EN 13501-6: Acidity none
Halogen-free No
ETIM for 644107 Batteries chargers and power cords (EC001576)
Feature Name
Feature Value
Number of cores (EF001792)
3
Nominal current (EF000001)
10 A
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)
None
Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)
None
Connection 2 (EF000322)
Other
Reaction-to-fire according to EN 13501-6: Class (EF011577)
None
Connection 1 (EF000321)
Other
System-oriented connector system (EF008067)
No
Nominal cross section conductor (EF000060)
1 mm²
Temperature resistance (EF003788)
-20 °C
Outer diameter approx. (EF003921)
7 mm
Material ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 644107 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.