

INDUSTRIAL COMPONENT DATA

644112 LEGRAND 10 CABLES C14-C13 LOCK 0.5M B

Brand: LEGRAND | Manufacturer Part Number: 644112



Manufacturer	LEGRAND
MPN / Reference	644112
Catalog number	644112
Category	Power cord
Minimum order	1 Pcs
Document ID	EO-A25AB51C4A
Generated	2026-07-31

Product Overview

10 CABLES C14-C13 LOCK 0.5M B

Set of 10 C14-C13 0.5m power cables with blue plug lock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > VARIOUS VDI

Additional Product Information

Power cables used to connect active equipment (servers) to a PDU. The unique C13 plug swivel mechanism that fits any standard C14 input prevents accidental disconnection from the server.

Connection 1 Other

Cable entry connection 1 Straight

Connection 2 Other

Cable entry connection 2 Straight

System of connectors connected to the system No

Number of threads 3

Nominal Conductor Section 1 mm²

Longitude 0.5 m

Cover material Polyvinyl chloride (PVC)

Temperature resistance -20-70 °C

Nominal intensity 10 A

Nominal Voltage 250-250 V

Outer Cover Color Blue

Coiled cable No

With cable switch No

Outer diameter approx. 7 mm

Reaction class to fire according to EN 13501-6 none

Reaction to fire according to EN 13501-6: Smoke production none

Reaction to fire according to EN 13501-6: Flammable drops/particles none

Reaction to fire according to EN 13501-6: Acidity none

Halogen-free No

ETIM for 644112 Batteries chargers and power cords (EC001576)

Feature Name

Feature Value

Number of cores (EF001792)

3

Nominal current (EF000001)

10 A

Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)

None

Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)

None

Connection 2 (EF000322)

Other

Reaction-to-fire according to EN 13501-6: Class (EF011577)

None

Connection 1 (EF000321)

Other

System-oriented connector system (EF008067)

No

Nominal cross section conductor (EF000060)

1 mm²

Temperature resistance (EF003788)

-20 °C

Outer diameter approx. (EF003921)

7 mm

Material ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 644112 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.