

INDUSTRIAL COMPONENT DATA

646101 LEGRAND PDU LK NO INT 19" 1P16A 8 C13

Brand: LEGRAND | Manufacturer Part Number: 646101



Manufacturer	LEGRAND
MPN / Reference	646101
Catalog number	646101
Category	Power distribution unit (PDU)
Minimum order	4 Pcs
Document ID	EO-D593D3DA8F
Generated	2026-08-03

Product Overview

PDU LK NO INT 19" 1P16A 8 C13

Smart PDU, Metered (Node Version), 19-inch, Single Phase 16 A, 8 C13 Outlets with Cable Lock, C20 Input
PDU MEASURED NODE 19 INCH, 1 PHASE 16A, 8 C13 SOCKETS WITH LOCK, IEC-320 C20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > PDU

Additional Product Information

Mounting Dimension (Standardized) 482.6 mm (19 inches)
Mounting Size 482.6 mm
Assembly Direction Horizontal
Electrical connection Outlet
Running the electrical connection C20
Number of phases 1
Cable length 0 m
Number of circuit breakers 0
Number of sockets with EEC 7/3 protective contact (type F) 0
Number of French Standard Sockets (Type E) 8
Number of sockets C13 8
Number of sockets C19 0
Number of C20 sockets 1
Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0
Number of Swiss Standard Type 15 Power Sockets 0
Number of Swiss Standard Type 23 sockets 0
Number of Swiss Standard Type 25 sockets 0
Number of RJ45 connectors 2
Number of USB connections 2
Number of other power outlets 0
Number of Height Units (AU) 1
Longitude 482.6 mm
Width 44.45 mm
Depth 115 mm
Nominal intensity 16 A
Supply voltage 230 V
With surge protection module No
Surge Category 2
EMC Filter No
Switchable No
With measuring device Yes
Control function No
SNMP Yes
With screen Yes
Evaluation Other
With LED indicator Yes
Fused No
Ammeter Yes
Temperature Measurement Yes
Includes mounting hardware Yes
Colour Black
Impact resistance Not applicable
Protection Class (IP) IP40
Operating Temperature -5-60 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal current 16-16 A
frequency 50-60 Hz
Display of markings on the connection terminals No
RAL number 9017
Connection Method Not applicable
Connection Cable Type Not applicable
Number of Circuit Breakers 0
Numbe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646101 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.