

INDUSTRIAL COMPONENT DATA

646104 LEGRAND PDU LK BA 0U 1P32A 20C13 4C19

Brand: LEGRAND | Manufacturer Part Number: 646104



Manufacturer	LEGRAND
MPN / Reference	646104
Catalog number	646104
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-D5B656A870
Generated	2026-07-28

Product Overview

PDU LK BA 0U 1P32A 20C13 4C19

Smart PDU, Measurement (Base Version), Zero-U, Single Phase 32 A, 20 C13 Outlets + 4 C19 Sockets, with Cable Lock
PDU BASE MEASURE 0U, 1 PHASE 32A, 20 C13+4 C19 LOCKING SOCKETS, IEC 60309

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > PDU
--------------	---------------

Additional Product Information

Mounting Dimension (Standardized) Metric

Mounting Size 1326 mm

Assembly Direction Vertical

Electrical connection Wired connector

Running the electrical connection EEC 32 A

Number of phases 1

Cable length 3 m

Number of circuit breakers 2

Number of sockets with EEC 7/3 protective contact (type F) 0

Number of French Standard Sockets (Type E) 24

Number of sockets C13 20

Number of sockets C19 4

Number of C20 sockets 0

Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0
Number of Swiss Standard Type 15 Power Sockets 0
Number of Swiss Standard Type 23 sockets 0
Number of Swiss Standard Type 25 sockets 0
Number of RJ45 connectors 2
Number of USB connections 0
Number of other power outlets 0
Longitude 1314 mm
Width 44.3 mm
Depth 65.9 mm
Nominal intensity 32 A
Supply voltage 230 V
With surge protection module No
Surge Category 2
EMC Filter No
Switchable No
With measuring device Yes
Control function No
SNMP Yes
With screen No
Evaluation Other
With LED indicator Yes
Fused No
Ammeter Yes
Temperature Measurement Yes
Includes mounting hardware Yes
Colour Black
Impact resistance Not applicable
Protection Class (IP) IP40
Operating Temperature -5-60 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal current 32-32 A
frequency 50-60 Hz
Display of markings on the connection terminals No
RAL number 9017
Connection Method Screw-on terminal
Terminal capacity 6-6 mm²
Connection Cable Type Flexible
Core cross-section 6-6 mm²
Maximum cable ent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646104 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.