

## INDUSTRIAL COMPONENT DATA

## 646106 LEGRAND PDU LK BA 0U 1P32A 24C13 12C19

Brand: LEGRAND | Manufacturer Part Number: 646106



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LEGRAND                       |
| MPN / Reference | 646106                        |
| Catalog number  | 646106                        |
| Category        | Power distribution unit (PDU) |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-49DBAB6A31                 |
| Generated       | 2026-08-03                    |

## Product Overview

PDU LK BA 0U 1P32A 24C13 12C19

Smart PDU, Metered (Base Version), Zero-U, Single Phase 32 A, 24 x HD C13 + 12 x C19 Sockets, with Cable Lock  
PDU HD BASE SIZE 0U, 1 PHASE 32A, 24 C13+12 C19 LOCKING SOCKETS, IEC 60309

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |               |
|--------------|---------------|
| Catalog path | LEGRAND > PDU |
|--------------|---------------|

## Additional Product Information

Mounting Dimension (Standardized) Metric

Mounting Size 1470 mm

Assembly Direction Vertical

Electrical connection Wired connector

Running the electrical connection EEC 32 A

Number of phases 1

Cable length 3 m

Number of circuit breakers 2

Number of sockets with EEC 7/3 protective contact (type F) 0

Number of French Standard Sockets (Type E) 36

Number of sockets C13 24

Number of sockets C19 12

Number of C20 sockets 0

Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0  
Number of Swiss Standard Type 15 Power Sockets 0  
Number of Swiss Standard Type 23 sockets 0  
Number of Swiss Standard Type 25 sockets 0  
Number of RJ45 connectors 2  
Number of USB connections 0  
Number of other power outlets 0  
Longitude 1458 mm  
Width 52 mm  
Depth 73.4 mm  
Nominal intensity 32 A  
Supply voltage 230 V  
With surge protection module No  
Surge Category 2  
EMC Filter No  
Switchable No  
With measuring device Yes  
Control function No  
SNMP Yes  
With screen No  
Evaluation Other  
With LED indicator Yes  
Fused No  
Ammeter Yes  
Temperature Measurement Yes  
Includes mounting hardware Yes  
Colour Black  
Impact resistance Not applicable  
Protection Class (IP) IP40  
Operating Temperature -5-60 °C  
Storage temperature -20-70 °C  
Type of voltage AC  
Nominal current 32-32 A  
frequency 50-60 Hz  
Display of markings on the connection terminals No  
RAL number 9017  
Connection Method Screw-on terminal  
Terminal capacity 6-6 mm<sup>2</sup>  
Connection Cable Type Flexible  
Core cross-section 6-6 mm<sup>2</sup>  
Maximum cable entr...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646106 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.