

INDUSTRIAL COMPONENT DATA

646113 LEGRAND PDU LK NO 0U 3P32A 24C13 12C19

Brand: LEGRAND | Manufacturer Part Number: 646113



Manufacturer	LEGRAND
MPN / Reference	646113
Catalog number	646113
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-99D42D2761
Generated	2026-08-03

Product Overview

PDU LK NO 0U 3P32A 24C13 12C19

Smart PDU, Metered (Node Version), Zero-U, Three-Phase 32A, 24 HD C13 Sockets + 12 C19 Sockets, Cable Lock
PDU HD MEASUREMENT NODE 0U, 3 PHASES 32A, 24 C13+12 C19 BLOCKING SOCKETS, IEC 60309

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > PDU
--------------	---------------

Additional Product Information

Mounting Dimension (Standardized) Metric

Mounting Size 1740 mm

Assembly Direction Vertical

Electrical connection Wired connector

Running the electrical connection EEC 32 A

Number of phases 3

Cable length 3 m

Number of circuit breakers 6

Number of sockets with EEC 7/3 protective contact (type F) 0

Number of French Standard Sockets (Type E) 36

Number of sockets C13 24

Number of sockets C19 12

Number of C20 sockets 0

Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0
Number of Swiss Standard Type 15 Power Sockets 0
Number of Swiss Standard Type 23 sockets 0
Number of Swiss Standard Type 25 sockets 0
Number of RJ45 connectors 2
Number of USB connections 2
Number of other power outlets 0
Longitude 1728 mm
Width 52 mm
Depth 91.4 mm
Nominal intensity 32 A
Supply voltage 415 V
With surge protection module No
Surge Category 2
EMC Filter No
Switchable No
With measuring device Yes
Control function No
SNMP Yes
With screen Yes
Evaluation Other
With LED indicator Yes
Fused No
Ammeter Yes
Temperature Measurement Yes
Includes mounting hardware Yes
Colour Black
Impact resistance Not applicable
Protection Class (IP) IP40
Operating Temperature -5-60 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal current 32-32 A
frequency 50-60 Hz
Display of markings on the connection terminals No
RAL number 9017
Connection Method Screw-on terminal
Terminal capacity 6-6 mm²
Connection Cable Type Flexible
Core cross-section 6-6 mm²
Maximum cable ent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646113 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.