

INDUSTRIAL COMPONENT DATA**646115 LEGRAND PDU LK NO 0U 3P32A 36C13 12C19**

Brand: LEGRAND | Manufacturer Part Number: 646115



Manufacturer	LEGRAND
MPN / Reference	646115
Catalog number	646115
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-82986787E5
Generated	2026-08-03

Product Overview

PDU LK NO 0U 3P32A 36C13 12C19

Smart PDU, Metered (Node Version), Zero-U, Three-Phase 32A, 36 HD C13 Sockets + 12 C19 Sockets, Cable Locked, Cable Locked

PDU HD COUNTER NODE 0U, 3 PHASES 32A, 36 C13+12 C19 BLOCKING SOCKETS, IEC 60309

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > PDU****Additional Product Information**

Mounting Dimension (Standardized) Metric

Mounting Size 1974 mm

Assembly Direction Vertical

Electrical connection Wired connector

Running the electrical connection EEC 32 A

Number of phases 3

Cable length 3 m

Number of circuit breakers 6

Number of sockets with EEC 7/3 protective contact (type F) 0

Number of French Standard Sockets (Type E) 48

Number of sockets C13 36

Number of sockets C19 12

Number of C20 sockets 0

Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0

Number of Swiss Standard Type 15 Power Sockets 0

Number of Swiss Standard Type 23 sockets 0

Number of Swiss Standard Type 25 sockets 0

Number of RJ45 connectors 2

Number of USB connections 2

Number of other power outlets 0

Longitude 1962 mm

Width 52 mm

Depth 91.4 mm

Nominal intensity 32 A

Supply voltage 415 V

With surge protection module No

Surge Category 2

EMC Filter No

Switchable No

With measuring device Yes

Control function No

SNMP Yes

With screen Yes

Evaluation Other

With LED indicator Yes

Fused No

Ammeter Yes

Temperature Measurement Yes

Includes mounting hardware Yes

Colour Black

Impact resistance Not applicable

Protection Class (IP) IP40

Operating Temperature -5-60 °C

Storage temperature -20-70 °C

Type of voltage AC

Nominal current 32-32 A

frequency 50-60 Hz

Display of markings on the connection terminals No

RAL number 9017

Connection Method Screw-on terminal

Terminal capacity 6-6 mm²

Connection Cable Type Flexible

Core cross-section 6-6 mm²

Maximum cable ent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646115 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.