

INDUSTRIAL COMPONENT DATA

646121 LEGRAND PDU LK I N 0U 1P16A 21C13 3C19

Brand: LEGRAND | Manufacturer Part Number: 646121



Manufacturer	LEGRAND
MPN / Reference	646121
Catalog number	646121
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-1B27C19C4F
Generated	2026-08-01

Product Overview

PDU LK I N 0U 1P16A 21C13 3C19

Smart PDU, Switched (Node Version), Zero-U, Single Phase 16A, 21 x C13 + 3 x C19 Sockets, with Cable Lock
PDU SWITCHED NODE 0U, 1 PHASE 16A, 21 C13+3 C19 BLOCKING SOCKETS, IEC-320 C20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > PDU
--------------	---------------

Additional Product Information

Mounting Dimension (Standardized) Metric

Mounting Size 1214 mm

Assembly Direction Vertical

Electrical connection Wired connector

Running the electrical connection C20

Number of phases 1

Cable length 0 m

Number of circuit breakers 0

Number of sockets with EEC 7/3 protective contact (type F) 0

Number of French Standard Sockets (Type E) 24

Number of sockets C13 21

Number of sockets C19 3

Number of C20 sockets 1

Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0
Number of Swiss Standard Type 15 Power Sockets 0
Number of Swiss Standard Type 23 sockets 0
Number of Swiss Standard Type 25 sockets 0
Number of RJ45 connectors 2
Number of USB connections 2
Number of other power outlets 0
Longitude 1202 mm
Width 44.3 mm
Depth 83.7 mm
Nominal intensity 16 A
Supply voltage 230 V
With surge protection module No
Surge Category 2
EMC Filter No
Switchable Yes
With measuring device Yes
Control function Yes
SNMP Yes
With screen Yes
Evaluation Other
With LED indicator Yes
Fused No
Ammeter Yes
Temperature Measurement Yes
Includes mounting hardware Yes
Colour Black
Impact resistance Not applicable
Protection Class (IP) IP40
Operating Temperature -5-60 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal current 16-16 A
frequency 50-60 Hz
Display of markings on the connection terminals No
RAL number 9017
Connection Method Not applicable
Connection Cable Type Not applicable
Number of Circuit Breakers 0
Number of residual current circuit break...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646121 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.