

**INDUSTRIAL COMPONENT DATA****646129 LEGRAND PDU LK I N 0U 3P16A 24C13 6C19**

Brand: LEGRAND | Manufacturer Part Number: 646129



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LEGRAND                       |
| MPN / Reference | 646129                        |
| Catalog number  | 646129                        |
| Category        | Power distribution unit (PDU) |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-1CC2226D25                 |
| Generated       | 2026-08-04                    |

**Product Overview**

PDU LK I N 0U 3P16A 24C13 6C19

Smart PDU, Switched (Node Version), Zero-U, Three-Phase 16A, 24 C13 Sockets + 6 C19 Sockets, with Cable Lock  
PDU SWITCHED NODE 0U, THREE-PHASE 16A, 24 C13+6 C19 BLOCKING JACKS, IEC 60309

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |               |
|--------------|---------------|
| Catalog path | LEGRAND > PDU |
|--------------|---------------|

**Additional Product Information**

Mounting Dimension (Standardized) Metric

Mounting Size 1554 mm

Assembly Direction Vertical

Electrical connection Wired connector

Running the electrical connection EEC 16 A

Number of phases 3

Cable length 3 m

Number of circuit breakers 0

Number of sockets with EEC 7/3 protective contact (type F) 0

Number of French Standard Sockets (Type E) 30

Number of sockets C13 24

Number of sockets C19 6

Number of C20 sockets 0

Number of sockets according to British standard (BS1363) 0

Number of Swiss Standard Type 13 sockets 0  
Number of Swiss Standard Type 15 Power Sockets 0  
Number of Swiss Standard Type 23 sockets 0  
Number of Swiss Standard Type 25 sockets 0  
Number of RJ45 connectors 2  
Number of USB connections 2  
Number of other power outlets 0  
Longitude 1542 mm  
Width 44.3 mm  
Depth 83.7 mm  
Nominal intensity 16 A  
Supply voltage 230 V  
With surge protection module No  
Surge Category 2  
EMC Filter No  
Switchable Yes  
With measuring device Yes  
Control function Yes  
SNMP Yes  
With screen Yes  
Evaluation Other  
With LED indicator Yes  
Fused No  
Ammeter Yes  
Temperature Measurement Yes  
Includes mounting hardware Yes  
Colour Black  
Impact resistance Not applicable  
Protection Class (IP) IP40  
Operating Temperature -5-60 °C  
Storage temperature -20-70 °C  
Type of voltage AC  
Nominal current 16-16 A  
frequency 50-60 Hz  
Display of markings on the connection terminals No  
RAL number 9017  
Connection Method Screw-on terminal  
Terminal capacity 2.5-2.5 mm<sup>2</sup>  
Connection Cable Type Flexible  
Core cross-section 2.5-2.5 mm<sup>2</sup>  
Maximu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 646129 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.