

## INDUSTRIAL COMPONENT DATA

## 660042BK LEGRAND U22REDONDA 100LM 1H P-NP BK

Brand: LEGRAND | Manufacturer Part Number: 660042BK



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 660042BK            |
| Catalog number  | 660042BK            |
| Category        | Emergency luminaire |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-FE120E4684       |
| Generated       | 2026-08-01          |

## Product Overview

U22REDONDA 100LM 1H P-NP BK

URA SPOT PRO emergency luminaire black color - 100 lumens - 1h - Permanent/Non-permanent

URA SPOT PRO black emergency luminaire - 100 lumens - 1h - P/NP

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |         |
|--------------|---------|
| Catalog path | LEGRAND |
|--------------|---------|

## Additional Product Information

Standard LED emergency luminaire - Permanent / Non-permanent (P/NP) - Black color - 200 lumens - Autonomy 1 hour -

LED - Ni-Cd battery - Maintenance tests are carried out manually.Type of mounting Installation

function Emergency Lighting/Pathway Identification

Suitable for labelling type Other

Type of indicator One side

With pictogram No

Suitable for standby switching Yes

Suitable for continuous circuit Yes

With remote switch connection No

With remote control No

Emergency function monitoring system none

Emergency Power Supply System Peripheral unit (single battery)

Battery quality NiCd

Lamp Non-interchangeable LED

With light source Yes  
Suitable for number of light sources 4  
Lamp holder none  
Number of light heads 1  
Housing material Plastic  
RAL number of the case 9005  
Housing color Black  
Cover material Plastic, opal  
Type of voltage AC/DC  
Nominal Voltage 230-230 V  
Nominal current 43-43 mA  
Type of control equipment Current-controlled LED service apparatus  
Light distributor Lens/Optics/Diffuser Panel  
Constant luminous flux regulation Yes  
Protection Class (IP) IP42  
Impact resistance IK07  
Protection class according to IEC 61140 II  
Luminaire with limited surface temperature "mark D" according to EN 60598-2-24 No  
Luminous flux in emergency mode 100 lm  
Nominal luminous flux according to IEC 62722-2-1 100-100 lm  
Max. system power 2.5 W  
Luminous flux in standby mode 100 lm  
Color Temperature 5000-5700 K  
Nominal Operating Time 1-1 hrs  
Height/Depth 44.5 mm  
Outer diameter 125 mm  
Mounting he...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660042BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.