

INDUSTRIAL COMPONENT DATA

660044 LEGRAND U22REDONDA 200LM 1H P-NP STD

Brand: LEGRAND | Manufacturer Part Number: 660044



Manufacturer	LEGRAND
MPN / Reference	660044
Catalog number	660044
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-EADED2ACE8
Generated	2026-07-29

Product Overview

U22REDONDA 200LM 1H P-NP STD

Emergency luminaire URA SPOT PRO - 200 lumens - 1h - Permanent / Non-permanent

URA SPOT PRO emergency luminaire - 200 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND
--------------	---------

Additional Product Information

Product features

Emergency lighting luminaire, URA SPOT PRO range of 200 lm and 1 hour of autonomy, with permanent / non-permanent operation. Product certified by AENOR with mark N. General features

URA SPOT PRO - LED emergency luminaires - Manufactured according to mandatory standard UNE-EN 60598-2-22 -

Product certified by AENOR with N mark - Non-permanent / permanent luminaires, according to wiring - IP 42 - IK 07 -

Control modes: standard and self-test (depending on models) - Autonomy: 1 and 2 hours (depending on models) - Power supply: 230 V $\pm$ 10% - 50/60 Hz. Class II - Green LED load teller - Removable and plug-in screw terminals with capacity 1x2, 5mm², both for power supply and remote control - Recessed installation in false ceiling - Opal diffuser

ETIM for 660044 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

1.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Built-in

Connection type (EF000124)

Screw connection

RAL-number housing (EF012502)

9003

Material cover (EF004284)

Plastic opal

Built-in height/depth (EF023518)

42 mm

With remote switch connection (EF007947)

No

Max. system power (EF009347)

2.3 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

200 lm

Suitable for number of light sources (EF006436)

4

Number of lighting heads (EF004...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660044 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.