

INDUSTRIAL COMPONENT DATA

660045BK LEGRAND U22REDONDA 350LM 1H P-NP BK

Brand: LEGRAND | Manufacturer Part Number: 660045BK



Manufacturer	LEGRAND
MPN / Reference	660045BK
Catalog number	660045BK
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-481F7F50DA
Generated	2026-08-01

Product Overview

U22REDONDA 350LM 1H P-NP BK

URA SPOT PRO emergency luminaire black color - 350 lumens - 1h - Permanent/Non-permanent

URA SPOT PRO black emergency luminaire - 350 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND
--------------	---------

Additional Product Information

Standard LED emergency luminaire - Permanent / Non-permanent (P/NP) - Black color - 200 lumens - Autonomy 2 hours -

LED - NiMh Battery - Maintenance tests are carried out manually.Type of mounting Installation

function Emergency Lighting/Pathway Identification

Suitable for labelling type Other

Type of indicator One side

With pictogram No

Suitable for standby switching Yes

Suitable for continuous circuit Yes

With remote switch connection No

With remote control No

Emergency function monitoring system none

Emergency Power Supply System Peripheral unit (single battery)

Battery quality NiCd

Lamp Non-interchangeable LED

With light source Yes
Suitable for number of light sources 8
Lamp holder none
Number of light heads 1
Housing material Plastic
RAL number of the case 9005
Housing color Black
Cover material Plastic, opal
Type of voltage AC/DC
Nominal Voltage 230-230 V
Nominal current 150-150 mA
Type of control equipment Current-controlled LED service apparatus
Light distributor Lens/Optics/Diffuser Panel
Constant luminous flux regulation Yes
Protection Class (IP) IP42
Impact resistance IK07
Protection class according to IEC 61140 II
Luminaire with limited surface temperature "mark D" according to EN 60598-2-24 No
Luminous flux in emergency mode 350 lm
Nominal luminous flux according to IEC 62722-2-1 350-350 lm
Max. system power 1.9 W
Luminous flux in standby mode 100 lm
Color Temperature 5000-5700 K
Nominal Operating Time 1-1 hrs
Height/Depth 44.5 mm
Outer diameter 125 mm
Mounting....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660045BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.