

## INDUSTRIAL COMPONENT DATA

## 660104 LEGRAND URANEXT NP 200LM 1H AUTOTEST

Brand: LEGRAND | Manufacturer Part Number: 660104



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 660104              |
| Catalog number  | 660104              |
| Category        | Emergency luminaire |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-6415B79344       |
| Generated       | 2026-07-28          |

## Product Overview

URANEXT NP 200LM 1H AUTOTEST

Emergency luminaire URA NEXT AUTOTEST- 200 lumens - 1h - Non-permanent

URA NEXTA UTOTEST emergency luminaire - 200 lumens - 1h - NP

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND

## Additional Product Information

## Product features

Emergency lighting luminaire, URA NEXT range of 200 lm and 1 hour of autonomy, with non-permanent operation Autotest.

Product certified by AENOR with mark N. General features

URA NEXT - LED emergency luminaires - Manufactured according to mandatory standard UNE-EN 60598-2-22 - Product certified by AENOR with N mark - Non-permanent and permanent luminaires. - IP 42 - IK 07 - Control modes: standard and self-test (depending on models) - Autonomy: 1 and 2 hours (depending on models) - Power supply: 230 V  $\pm$  10% - 50/60 Hz. Class II - Green LED load teller - Removable and plug-in screw terminals with capacity 1x2.5mm<sup>2</sup>, both for power supply and remote control - Surface installation or recessed in false ceiling with accessory 660190 - 5 cable inputs: 1 open at the back and 4 demountable Ø20mm for hose or rigid tube inlet - Opal diffuser -

ETIM for 660104 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

1.5 mm<sup>2</sup>

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted / ceiling surface mounting

Connection type (EF000124)

Screw connection

RAL-number housing (EF012502)

9003

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

1.9 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660104 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.