

**INDUSTRIAL COMPONENT DATA**

# 660107 LEGRAND URANEXT NP 200LM 2H AUTOTEST

Brand: LEGRAND | Manufacturer Part Number: 660107



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 660107              |
| Catalog number  | 660107              |
| Category        | Emergency luminaire |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-D00AF259A1       |
| Generated       | 2026-08-02          |

## Product Overview

URANEXT NP 200LM 2H AUTOTEST

Emergency luminaire URA NEXT AUTOTEST- 200 lumens - 2h - Non-permanent

URA NEXTA UTOTEST emergency luminaire - 200 lumens - 2h - NP

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |         |
|--------------|---------|
| Catalog path | LEGRAND |
|--------------|---------|

## Additional Product Information

**Product features**

Emergency lighting luminaire, URA NEXT range of 200 lm and 2 hours of autonomy, with non-permanent operation

Autotest. Product certified by AENOR with mark N. General features

URA NEXT - LED emergency luminaires - Manufactured according to mandatory standard UNE-EN 60598-2-22 - Product certified by AENOR with N mark - Non-permanent and permanent luminaires. - IP 42 - IK 07 - Control modes: standard and self-test (depending on models) - Autonomy: 1 and 2 hours (depending on models) - Power supply: 230 V  $\pm$  10% - 50/60 Hz. Class II - Green LED load teller - Removable and plug-in screw terminals with capacity 1x2.5mm<sup>2</sup>, both for power supply and remote control - Surface installation or recessed in false ceiling with accessory 660190 - 5 cable inputs: 1 open at the back and 4 demountable Ø20mm for hose or rigid tube inlet - Opal diffuser -

ETIM for 660107 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

1.5 mm<sup>2</sup>

With remote control (EF000483)  
No  
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)  
No  
Lamp type (EF002423)  
LED non-replaceable  
Mounting method (EF000003)  
Wall surface mounted / ceiling surface mounting  
Connection type (EF000124)  
Screw connection  
RAL-number housing (EF012502)  
9003  
Material cover (EF004284)  
Plastic opal  
With remote switch connection (EF007947)  
No  
Max. system power (EF009347)  
0.4 W  
Colour temperature (EF009346)  
5000 K  
Rated luminous flux according to IEC 62722-2-1 (EF...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660107 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.