INDUSTRIAL COMPONENT DATA

660145 LEGRAND U22REDON 350LM 1H P-NP AUTO

Brand: LEGRAND | Manufacturer Part Number: 660145

Manufacturer	LEGRAND
MPN / Reference	660145
Catalog number	660145
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-9B2475360C
Generated	2026-07-29

Product Overview

U22REDON 350LM 1H P-NP AUTO
Emergency luminaire URA SPOT PRO AUTOTEST- 350 lumens - 1h - Permanent / Non-permanent
URA SPOT PROA UTOTEST emergency luminaire - 350 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND

Additional Product Information

Product features
Emergency lighting luminaire, URA SPOT PRO range of 350 lm and 1 hour of autonomy, with permanent / non-permanent operation, Autotest. Product certified by AENOR with mark N. General features
URA SPOT PRO - LED emergency luminaires - Manufactured according to mandatory standard UNE-EN 60598-2-22 - Product certified by AENOR with N mark - Non-permanent / permanent luminaires, according to wiring - IP 42 - IK 07 - Control modes: standard and self-test (depending on models) - Autonomy: 1 and 2 hours (depending on models) - Power supply: 230 V ± 10% - 50/60 Hz. Class II - Green LED load teller - Removable and plug-in screw terminals with capacity 1x2, 5mm2, both for power supply and remote control - Recessed installation in false ceiling - Opal diffuser
ETIM for 660145 Luminaires (EC001957)
Feature Name
Feature Value
Conductor cross section (EF000085)
1.5 mm²
With remote control (EF000483)

No
Luminaire with limited surface temperature, sign "D“ according to EN 60598-2-24 (EF006420)
No
Lamp type (EF002423)
LED non-replaceable
Mounting method (EF000003)
Built-in
Connection type (EF000124)
Screw connection
RAL-number housing (EF012502)
9003
Material cover (EF004284)
Plastic opal
Built-in height/depth (EF023518)
42 mm
With remote switch connection (EF007947)
No
Max. system power (EF009347)
1.9 W
Colour temperature (EF009346)
5000 K
Rated luminous flux according to IEC 62722-2-1 (EF009349)
350 lm
Suitable for number of light sources (EF006436)
8
Number of lighting he...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660145 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.