

INDUSTRIAL COMPONENT DATA

660427 LEGRAND B65LED 200LM 1H IP65 NP AUTOTE

Brand: LEGRAND | Manufacturer Part Number: 660427



Manufacturer	LEGRAND
MPN / Reference	660427
Catalog number	660427
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-6553E62D85
Generated	2026-08-03

Product Overview

B65LED 200LM 1H IP65 NP AUTOTE

Emergency luminaire B65 Led AUTOTEST - 200 lumens - 1 h - Non-permanent

UTOTEST B65LEDA emergency luminaire - 200 lumens - 1h - IP65 - NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > WATERTIGHT EMERGENCIES

Additional Product Information

Product features

EMERGENCY luminaire LED AUTOTEST - Non-permanent (NP) - 200 lumens - Autonomy 1 hour - LED - Ni-Cd battery - The luminaire performs a weekly automatic test that checks the condition of the lamp and a quarterly automatic test that checks the condition of the battery. - Communicates its status using the LED (green and yellow) signalling. General features B65LED - Watertight self-test LED emergency luminaires - Manufactured according to UNE-EN 60598-2-22 standards - Non-permanent luminaires - LED with half-life of 150,000h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Green led load indicator - Automatic terminals of large capacity 2x2,5mm² - Remote control bornas for rest - Opal diffuser - 3 flexible material inputs for tube Ø16,20,25mm - Surface installation

ETIM for 660427 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

1.7 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

200 lm

Suitable for number of light sources (EF006436)

4

Nominal current (EF009345)

7.3 mA

Impact strength (EF004293)

IK07

Mo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660427 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.