

INDUSTRIAL COMPONENT DATA

660460 LEGRAND 1000LM 1H NP AUT LED PROJECTOR

Brand: LEGRAND | Manufacturer Part Number: 660460



Manufacturer	LEGRAND
MPN / Reference	660460
Catalog number	660460
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-2976C37047
Generated	2026-08-02

Product Overview

1000LM 1H NP AUT LED PROJECTOR

Black LED projector A utotest 1000 lumens - 1 spotlight - IP65

1000 lumens 1H LED Projector. NPA utotest

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > WATERTIGHT EMERGENCIES

Additional Product Information

Standalone LED emergency lighting projector - 1 spotlight - 1000 lumens - Autonomy 1 hour - IP65 - IK07 - Manufactured according to mandatory standard UNE EN 60 598 - 2-22 - Certified with AENOR and ENEC Mark N - Class II - Not permanent - Self-test - Power supply: 230 V± - 50/60 Hz - Batteries: LiFePO4 - Equipped with 1x2.5mm² automatic connection terminals - Green charge indicator LED - Standby by remote controlType of mounting Wall extension function Emergency Lighting/Pathway Identification

Suitable for labelling type Other

With pictogram No

Suitable for standby switching Yes

Suitable for continuous circuit No

With remote switch connection No

With remote control Yes

Emergency function monitoring system Automatic self-test

Emergency Power Supply System Peripheral unit (single battery)

Battery quality Lithium-ion

Lamp Non-interchangeable LED
With light source Yes
Suitable for number of light sources 4
Lamp holder none
Number of light heads 1
Housing material Plastic
RAL number of the case 9011
Housing color Black
Cover material Plastic, transparent
Type of voltage AC
Nominal Voltage 207-253 V
Nominal current 10-29 mA
Type of control equipment Current-controlled LED service apparatus
Interchangeable control equipment No
Light distributor Refractor lens
Constant luminous flux regulation Yes
Protection Class (IP) IP65
Impact resistance IK07
Protection class according to IEC 61140 II
Luminous flux in emergency mode 1000 lm
Nominal luminous flux according to IEC 62722-2-1 1000-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660460 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.