

INDUSTRIAL COMPONENT DATA

660463 LEGRAND 2500LM 1H NP AUT LED PROJECTOR

Brand: LEGRAND | Manufacturer Part Number: 660463



Manufacturer	LEGRAND
MPN / Reference	660463
Catalog number	660463
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-2CFDB0AED0
Generated	2026-07-29

Product Overview

2500LM 1H NP AUT LED PROJECTOR

Black LED projector A utotest 2500 lumens - 2 spotlights - IP65

LED projector 2500 lumens 1H. NPA utotest

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > WATERTIGHT EMERGENCIES

Additional Product Information

Standalone LED emergency lighting projector - 2 spotlights - 1500 lumens - Autonomy 1 hour - IP65 - IK07 - Manufactured according to mandatory standard UNE EN 60 598 - 2-22 - Certified with N Mark of AENOR and ENEC - Class II - Not permanent- Self-test - Power supply: 230 V $\pm$ - 50/60 Hz - Batteries: LiFePO4 - Equipped with automatic connection terminals of 1x2.5mm²- Green charge indicator LED - Standby by remote controlType of mounting Wall extension function Emergency Lighting/Pathway Identification

Suitable for labelling type Other

With pictogram No

Suitable for standby switching Yes

Suitable for continuous circuit No

With remote switch connection No

With remote control Yes

Emergency function monitoring system Automatic self-test

Emergency Power Supply System Peripheral unit (single battery)

Battery quality Lithium-ion

Lithium-ion battery type Lithium iron phosphate (LifePo4)
With battery heating element No
Lamp Non-interchangeable LED
With light source Yes
Suitable for number of light sources 8
Lamp holder none
Number of light heads 2
Housing material Plastic
RAL number of the case 9011
Housing color Black
Cover material Plastic, transparent
Type of voltage AC
Nominal Voltage 207-253 V
Nominal current 12-58 mA
Type of control equipment Current-controlled LED service apparatus
Interchangeable control equipment No
Light distributor Refractor lens
Constant luminous flux regulation Yes
Protection Class (IP) IP65
Impact resistance IK07
Protection class according to IEC 61140 li...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660463 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.