

INDUSTRIAL COMPONENT DATA

660601PL LEGRAND URA21PLUS 70LM 1H NP AUTOTEST

Brand: LEGRAND | Manufacturer Part Number: 660601PL



Manufacturer	LEGRAND
MPN / Reference	660601PL
Catalog number	660601PL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-7BB22FA926
Generated	2026-08-03

Product Overview

URA21PLUS 70LM 1H NP AUTOTEST

Emergency luminaire URA21LED PLUS AUTOTEST- 70 lumens - 1h - Non-permanent

URA21 LED PLUSA UTOTEST Emergency Luminaire - 70 lumens - 1h - NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > NEW URA21 EMERGENCIES / LED

Additional Product Information

Product features

EMERGENCY luminaire LED AUTOTEST - Non-permanent (NP) - 70 lumens - Autonomy 1 hour - LED - Ni-Cd battery - The luminaire performs a weekly automatic test that checks the condition of the lamp and an automatic quarterly test that checks the battery status. - Communicates its status using the LED (green and yellow) signalling. General features URA21LED PLUS - Indoor AUTOTEST LED Emergency Luminaires - Manufactured according to UNE-EN 60598-2-22 - Non-permanent luminaires - LED with half-life of 150,000h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Green and Yellow Signaling Leds - 2x2.5mm² Large Capacity Automatic Terminals - Remote Control Terminals for Resting - Surface or Recessed Installation - 4 cable inputs. 1 open on the back and 3 dephionables of 20mm for hose inlet or rigid tube - Opal diffuser - Fully recyclable at the end of its life

ETIM for 660601PL Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Power factor (EF025740)

0.5

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

1.3 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

70....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660601PL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.