

INDUSTRIAL COMPONENT DATA

660625 LEGRAND URAONE 500LM 1H IP42 NP AUTOTE

Brand: LEGRAND | Manufacturer Part Number: 660625



Manufacturer	LEGRAND
MPN / Reference	660625
Catalog number	660625
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-60355CBE74
Generated	2026-08-02

Product Overview

URAONE 500LM 1H IP42 NP AUTOTE

Emergency luminaire URAONE AUTOTEST- 500 lumens - 1 h - Non-permanent

URAONEA UTOTEST emergency luminaire - 500 lumens - 1h - NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND

Additional Product Information

Product features

EMERGENCY luminaire LED AUTOTEST - Non-permanent (NP) - 500 lumens - Autonomy 1 hour - LED - Ni-Mh battery - The luminaire performs a weekly automatic test that checks the condition of the lamp and a quarterly automatic test that checks the battery status. - Communicates its status using the LED (green and yellow) signalling. General features URA ONE - Indoor self-test LED emergency luminaires - Manufactured according to UNE-EN 60598-2-22 standards - Non-permanent luminaires - LED with average life of 150,000h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Green Led Load Witness - 2x2.5mm² Large Capacity Automatic Terminals - Lift Terminals for Resting - Surface Installation, Recessed, Banner or Suspension - Opal Diffuser - Fully Recyclable at the End of Life ETIM for 660625 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

2.7 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

500 lm

Suitable for number of light sources (EF006436)

2

Nominal current (EF009345)

5.6 mA

Impact strength (EF004293)

IK...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 660625 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.