

INDUSTRIAL COMPONENT DATA

661245 LEGRAND URA 34 LED 450LM 1H IP42 P/NP

Brand: LEGRAND | Manufacturer Part Number: 661245



Manufacturer	LEGRAND
MPN / Reference	661245
Catalog number	661245
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-95CEAF6E82
Generated	2026-08-02

Product Overview

URA 34 LED 450LM 1H IP42 P/NP

Luminaire emergency URA34LED - 450 lumens - 1 hr - Permanent/Non-Permanent

URA34 LED emergency luminaire - 450 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > PRESCRIPTION OF EMERGENCIES**

Additional Product Information

Product features

Luminaire emergency standard LED - Permanent / Non-permanent (P/NP) - 450 lumens - Autonomy 1 hour - LED - Ni-MH Battery - The test of maintenance is carried out manually General characteristics

URA34LED - Luminaires for emergency indoor LED - Built according to the standards UNE-EN 60598-2-22 - Luminaires for permanent / non-permanent depending on the wiring done - Flux of 120 lumens in a permanent way - LED with average life in a permanent way 100,000 h - IP 42 - IK 07 - Power supply: 230 V ± 10 % - 50/60 Hz. Class II - Source-switched low-energy consumption - green Led witness of charge - For installation on a surface to add the plug-in socket ref. 6612 80 - For recessed installation in false ceiling to add to the framework recessed ref.6612 95 - Terminals of remote control to set at rest - opal Diffuser - Completely recyclable at the end of its useful life

ETIM for 661245 Luminaires (EC001957)

Feature Name

Feature Value

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)
Wall surface mounted
Material cover (EF004284)
Plastic transparent
With remote switch connection (EF007947)
No
Max. system power (EF009347)
45 W
Colour temperature (EF009346)
5700 K
Rated luminous flux according to IEC 62722-2-1 (EF009349)
450 lm
Nominal current (EF009345)
200 mA
Monitoring equipment (EF008091)
None
Protection class according to IEC 61140 (EF000004)
II
Lamp holder (EF000048)
Other
Height/depth (EF001456)
55 mm
Width (EF000008)
125 mm
Degree of protection....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661245 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.