

INDUSTRIAL COMPONENT DATA

661425 LEGRAND B65LED 70LM 1H IP65 NP

Brand: LEGRAND | Manufacturer Part Number: 661425



Manufacturer	LEGRAND
MPN / Reference	661425
Catalog number	661425
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-4A84014F9B
Generated	2026-08-02

Product Overview

B65LED 70LM 1H IP65 NP

Emergency luminaire B65 Led - 70 lumens - 1 h - Non-permanent

B65LED Emergency Luminaire - 70 lumens - 1h - IP65 - NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > WATERTIGHT EMERGENCIES
--------------	----------------------------------

Additional Product Information

Product features

Standard LED emergency luminaire - Non-permanent (NP) - 70 lumens - Autonomy 1 hour - IP65 - LED - Ni-Cd battery -

Maintenance tests are performed manually General features

B65LED - Watertight LED Emergency Luminaires - Manufactured according to UNE-EN 60598-2-22 standards -

Permanent/non-permanent luminaires depending on the wiring performed - 100 lumen flow Permanent mode - LED with half-life of 150,000h - IP 65 - IK 07 - Power supply: 230 V ± 10 % - 50/60 Hz. Class II - Green Led Load Witness -

2x2.5mm² Large Capacity Automatic Terminals - Laying Remote Control Terminals - Opal Diffuser - 3 Flexible Tube

Material Inches - 16,20,25mm - Surface Installation

ETIM for 661425 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

1.3 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

70 lm

Suitable for number of light sources (EF006436)

4

Nominal current (EF009345)

5.6 mA

Impact strength (EF004293)

IK07

Monitoring equipment (EF008091)

Automatic self test

Protection class according to IEC 61140 (EF000004)

II

Lamp holder (EF00004...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661425 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.