

INDUSTRIAL COMPONENT DATA

661427 LEGRAND B65LED 200LM 1H IP65 NP

Brand: LEGRAND | Manufacturer Part Number: 661427



Manufacturer	LEGRAND
MPN / Reference	661427
Catalog number	661427
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-E17E6D98FE
Generated	2026-08-02

Product Overview

B65LED 200LM 1H IP65 NP

Emergency luminaire B65 Led - 200 lumens - 1 h - Non-permanent

B65LED Emergency Luminaire - 200 lumens - 1h - IP65 - NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > WATERTIGHT EMERGENCIES
--------------	----------------------------------

Additional Product Information

Product features

Standard LED emergency luminaire - Non-permanent (NP) - 200 lumens - Autonomy 1 hour - IP65 - LED - Ni-Cd battery -

Maintenance tests are performed manually General features

B65LED - Watertight LED Emergency Luminaires - Manufactured according to UNE-EN 60598-2-22 standards -

Permanent/non-permanent luminaires depending on the wiring performed - 100 lumen flow Permanent mode - LED with

half-life of 150,000h - IP 65 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Green Led Load Witness -

2x2.5mm² Large Capacity Automatic Terminals - Laying Remote Control Terminals - Opal Diffuser - 3 Flexible Tube

Material Inches - 16,20,25mm - Surface Installation

ETIM for 661427 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Lamp type (EF002423)
LED replaceable
Mounting method (EF000003)
Wall surface mounted
Connection type (EF000124)
Other
Material cover (EF004284)
Plastic opal
With remote switch connection (EF007947)
No
Max. system power (EF009347)
2.2 W
Colour temperature (EF009346)
5000 K
Rated luminous flux according to IEC 62722-2-1 (EF009349)
200 lm
Suitable for number of light sources (EF006436)
4
Nominal current (EF009345)
9.5 mA
Impact strength (EF004293)
IK07
Monitoring equipment (EF008091)
Automatic self test
Protection class according to IEC 61140 (EF000004)
II
Lamp holder (EF000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661427 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.