

INDUSTRIAL COMPONENT DATA

661434 LEGRAND B65LED 350LM 1H IP65 P/NP

Brand: LEGRAND | Manufacturer Part Number: 661434



Manufacturer	LEGRAND
MPN / Reference	661434
Catalog number	661434
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-981E0E4393
Generated	2026-08-03

Product Overview

B65LED 350LM 1H IP65 P/NP

Emergency luminaire B65 - standard maintained / non maintained - 350 lm - 1h - LED

B65LED Emergency Luminaire - 350 lumens - 1h - IP65 - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > WATERTIGHT EMERGENCIES
--------------	----------------------------------

Additional Product Information

Pack (number of units)1

Volume (dm3)2.497

Weight (g)735.00

Product characteristicsStandard luminaires - Maintained/Non-maintained (M/NM)

Standard luminaires require normal lighting manual switching off in order to test emergency lighting

These Maintained luminaires can also operate in Non-maintained mode according to the wiring of normal lighting

350 lm - 1h (LEDs)

General characteristicsB65 LED - weatherproof self-contained emergency lighting luminaire LEDWeatherproof LED maintained and non-maintained units

Certified to IEC and EN 60598-2-22 standards

High power LEDs. IP 65 - IK 07

Plug-in base to ease fixing, cabling and connection

Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours

Charge monitor with a green LED. Power supply: 230 V ± 10%- 50/60 Hz. Class II

High-capacity screw terminals (2 x 2.5mm²)

3 flexible cable entries for Ø16, 20 and 25 mm tubes

Can be equipped with metallic protection grids Cat.Nos 0 626 90/92

ETIM for 661434 Luminares (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Screw connection

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

35 W

Colour temperature (EF009346)

5700 K

Rated luminous fl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661434 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.