

INDUSTRIAL COMPONENT DATA

661453 LEGRAND LED PROJECTOR 2500LM 1H NP

Brand: LEGRAND | Manufacturer Part Number: 661453



Manufacturer	LEGRAND
MPN / Reference	661453
Catalog number	661453
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-F1E4BE63F4
Generated	2026-08-02

Product Overview

LED PROJECTOR 2500LM 1H NP

Standard LED emergency luminaire Twinspot - non autotest - 2 x 1250 lm - 1h

LED projector 2500 lumens - 2 spotlights - IP55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > WATERTIGHT EMERGENCIES**

Additional Product Information

Pack (number of units)1

Volume (dm3)14.07

Weight (g)4 085.00

Product characteristicsStandard LED spotlight luminaires - Non-Maintained (NM)

2 x 1250 lm - 1h

General characteristicsLED Twinspot emergency lighting luminairesHigh performance LED non maintained emergency lighting luminaires

Certified to IEC and EN 60598-2-22 standards

High power LEDs spotlights with optimized lighting distribution

Low consumption electronic switching power supply

High capacity terminals: 2 x 2.5 mm² - IP 55 - IK 07

Duration: 1, 2 and 3 hours. Ni-Cd batteries. Recharge time: 24h

Green charge indicator with high luminosity LED, to improve visibility from the floor when high installation

Power supply: 230 V~ ± 10% - 50/60 Hz. Class II

Rest mode with remote control device Cat.No 0 039 01 to avoid battery discharge in case of voluntary power cut

Surface mounting installation with 4 wall-mounting lugs (Cat.No 0 358 02, supplied) or 4 screws (not supplied)

ETIM for 661453 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Screw connection

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

250 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661453 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.