

INDUSTRIAL COMPONENT DATA

661463 LEGRAND LED PROJECTOR 2500LM 1H NP STD

Brand: LEGRAND | Manufacturer Part Number: 661463



Manufacturer	LEGRAND
MPN / Reference	661463
Catalog number	661463
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-044C1C131F
Generated	2026-07-29

Product Overview

LED PROJECTOR 2500LM 1H NP STD

Black LED projector 2500 lumens - 2 spotlights - IP65

LED Projector 2500 lumens 1H. NP Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > WATERTIGHT EMERGENCIES

Additional Product Information

Standalone LED emergency lighting projector - 2 spotlights - 1500 lumens - Autonomy 1 hour - IP65 - IK07 - Manufactured according to mandatory standard UNE EN 60 598 - 2-22 - Certified with N Mark of AENOR and ENEC - Class II -

Non-permanent - Standard - Power supply: 230 V± - 50/60 Hz - Batteries: LiFePO4 - Equipped with automatic connection terminals of 1x2.5mm² - Green charge indicator LED - Standby by remote controlType of mounting Wall extension function Emergency Lighting/Pathway Identification

Suitable for labelling type Other

With pictogram No

Suitable for standby switching Yes

Suitable for continuous circuit No

With remote switch connection No

With remote control Yes

Emergency function monitoring system Test button

Emergency Power Supply System Peripheral unit (single battery)

Battery quality Lithium-ion

Lamp Non-interchangeable LED
With light source Yes
Suitable for number of light sources 8
Lamp holder none
Number of light heads 2
Housing material Plastic
RAL number of the case 9011
Housing color Black
Cover material Plastic, transparent
Type of voltage AC
Nominal Voltage 207-253 V
Nominal current 12-62 mA
Type of control equipment Current-controlled LED service apparatus
Interchangeable control equipment No
Light distributor Refractor lens
Constant luminous flux regulation Yes
Protection Class (IP) IP65
Impact resistance IK07
Protection class according to IEC 61140 II
Luminous flux in emergency mode 2500 lm
Nominal luminous flux according to IEC 62722-2-1 2500-25...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661463 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.