

INDUSTRIAL COMPONENT DATA

661600PL LEGRAND URA21PLUS 50LM 1H NP

Brand: LEGRAND | Manufacturer Part Number: 661600PL



Manufacturer	LEGRAND
MPN / Reference	661600PL
Catalog number	661600PL
Category	Emergency luminaire
Minimum order	10 Pcs
Document ID	EO-BD75F82E6F
Generated	2026-08-03

Product Overview

URA21PLUS 50LM 1H NP

Emergency luminaire URA21LED PLUS - 50 lumens - 1h - Non-permanent

URA21 LED PLUS emergency luminaire - 50 lumens - 1h - NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > NEW URA21 EMERGENCIES / LED
--------------	---------------------------------------

Additional Product Information

Product features

Standard LED emergency luminaire - Non-permanent (NP) - 50 lumens - Autonomy 1 hour - LED - Ni-Cd battery -

Maintenance tests are performed manually General features

URA21LED PLUS- Indoor LED emergency luminaires - Manufactured according to UNE-EN 60598-2-22 standards -

Permanent/non-permanent luminaires depending on the wiring performed - Flow of 100 lumens in permanent mode - LED with half-life OF 150,000h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Low power switched source in P/NP models - Green LED load indicator - 2x2.5mm² large capacity automatic terminals - Remote control terminals for resting - Surface or recessed installation - 4 cable inputs. 1 open on the back and 3 dephonables of 20mm for hose inlet or rigid tube - Opal diffuser - Fully recyclable at the end of its life

ETIM for 661600PL Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Power factor (EF025740)

0.5

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

1.3 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

70 lm

Suitable for number of light sources (EF006436)

4

Number....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661600PL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.