

INDUSTRIAL COMPONENT DATA

661610PL LEGRAND URA21PLUS 100LM 3H P/NP

Brand: LEGRAND | Manufacturer Part Number: 661610PL



Manufacturer	LEGRAND
MPN / Reference	661610PL
Catalog number	661610PL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-59FB660759
Generated	2026-07-31

Product Overview

URA21PLUS 100LM 3H P/NP

Emergency luminaire URA21LED PLUS - 100 lumens - 3h - Permanent/Non-permanent

URA21 LED PLUS emergency luminaire - 100 lumens - 3h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > NEW URA21 EMERGENCIES / LED
--------------	---------------------------------------

Additional Product Information

Product features

Standard LED emergency luminaire - Permanent/Non-permanent (P/NP) - 100 lumens - Autonomy 3 hours - LED - Ni-Cd battery - Maintenance tests are carried out manually

General features

URA21LED PLUS- Indoor LED emergency luminaires - Manufactured according to UNE-EN 60598-2-22 standards - Permanent/non-permanent luminaires depending on the wiring performed - Flow of 100 lumens in permanent mode - LED with half-life OF 150,000h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Low power switched source in P/NP models - Green LED load indicator - 2x2.5mm² large capacity automatic terminals - Remote control terminals for resting - Surface or recessed installation - 4 cable inputs. 1 open on the back and 3 dephonables of 20mm for hose inlet or rigid tube - Opal diffuser - Fully recyclable at the end of its life

ETIM for 661610PL Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Power factor (EF025740)

0.5

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

100 lm

Suitable for number of light sources (EF006436)

4

Number of lighting heads....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661610PL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.