

**INDUSTRIAL COMPONENT DATA**

# 661617PL LEGRAND URA21PLUS 160LM 1H NP 120V

Brand: LEGRAND | Manufacturer Part Number: 661617PL



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 661617PL            |
| Catalog number  | 661617PL            |
| Category        | Emergency luminaire |
| Minimum order   | 10 Pcs              |
| Document ID     | EO-E77D924F65       |
| Generated       | 2026-08-04          |

## Product Overview

URA21PLUS 160LM 1H NP 120V

Emergency luminaire URA21LED PLUS - 120 V- 160 lumens - 1h - Non-permanent

URA21 LED PLUS emergency luminaire - 120V - 160 lumens - 1h - NP

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                       |
|--------------|---------------------------------------|
| Catalog path | LEGRAND > NEW URA21 EMERGENCIES / LED |
|--------------|---------------------------------------|

## Additional Product Information

**Product features**

Standard LED emergency luminaire - 120 V -Non-permanent (NP) - 160 lumens - Autonomy 1 hour - LED - Ni-Cd battery -

Maintenance tests are performed manually General features

URA21LED PLUS- Indoor LED emergency luminaires - Manufactured according to UNE-EN 60598-2-22 standards -

Permanent/non-permanent luminaires depending on the wiring performed - Flow of 100 lumens in permanent mode - LED with half-life OF 150,000h - IP 42 - IK 07 - Power supply: 230 V  $\pm$  10 % - 50/60 Hz. Class II - Low power switched source in P/NP models - Green LED load indicator - 2x2.5mm<sup>2</sup> large capacity automatic terminals - Remote control terminals for resting - Surface or recessed installation - 4 cable inputs. 1 open on the back and 3 dephonables of 20mm for hose inlet or rigid tube - Opal diffuser - Fully recyclable at the end of its life

ETIM for 661617PL Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm<sup>2</sup>

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non-replaceable

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Other

Power factor (EF025740)

0.5

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

2.2 W

Colour temperature (EF009346)

5000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

160 lm

Suitable for number of light sources (EF006436)....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661617PL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.