

INDUSTRIAL COMPONENT DATA

661642 LEGRAND URAONE 200LM 2H IP42 P/NP

Brand: LEGRAND | Manufacturer Part Number: 661642



Manufacturer	LEGRAND
MPN / Reference	661642
Catalog number	661642
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-B205B95128
Generated	2026-08-03

Product Overview

URAONE 200LM 2H IP42 P/NP

Luminaire emergency URA ONE - 200 lumens - 2 h - Permanent /Non-Permanent

URA ONE Emergency Luminaire - 200 lumens - 2h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND

Additional Product Information

Product features

Luminaire emergency standard LED - Permanent / Non-permanent (P/NP) - 200 lumens - Autonomy 2 hours - LED -

Battery-Ni-Cd - The test of maintenance is carried out manually General characteristics

URA ONE - Luminaires for emergency indoor LED - Built according to the standards UNE-EN 60598-2-22 - Luminaires for permanent / non-permanent depending on the wiring done - Flux of 100 lumens in a permanent way - LED with average life in a permanent way 150,000 h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Source-switched low-energy consumption model-P/NP - green Led witness of load - Terminal automatic high-capacity 2x2,5mm² - Terminal remote control to set at rest - on surface mounting, recessed, banner or suspension - opal Diffuser - Completely recyclable at the end of its useful life

ETIM for 661642 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

Fluorescent lamp

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Screw connection

Material cover (EF004284)

Plastic opal

With remote switch connection (EF007947)

No

Max. system power (EF009347)

20 W

Colour temperature (EF009346)

5700 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

200 lm

Number of lighting heads (EF004258)

1

Nominal current (EF009345)

87 mA

Impact stre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 661642 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.