

INDUSTRIAL COMPONENT DATA

662242 LEGRAND URA 34 LED LVS2 150LM 1H P/NP

Brand: LEGRAND | Manufacturer Part Number: 662242



Manufacturer	LEGRAND
MPN / Reference	662242
Catalog number	662242
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-18C69298C8
Generated	2026-08-04

Product Overview

URA 34 LED LVS2 150LM 1H P/NP

Luminaire emergency URA34LED LVS2-150 lumens-1 hr-Permanent/Non-Permanent

URA34 LED L. VS2 Emergency Luminaire - 150 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

LEGRAND > PRESCRIPTION OF EMERGENCIES

Additional Product Information

Product features

Luminaire emergency LED auto-test / centralized (LVS2) - Permanent / Non-permanent (P/NP) - 150 lumens - Autonomy 1 hour - LED - Ni-MH Battery - The luminaire performs a self-test weekly to check the status of the lamp, and a self-test quarterly to verify the status of the battery. - Communicates its status using the leds (green and yellow) signaling - For operation in modes of centralized and self-test. The centralized mode is active by giving a code to each fixture and wiring the emergency to the bus line. General characteristics

URA34 LVS2 - Luminaires for emergency LED auto-test / centralized for indoor - Manufactured according to standards UNE-en 60598-2-22 - Luminaires for permanent / non-permanent depending on the wiring done - Flux of 120 lumens in a permanent way - LED with average life in a permanent way 100,000 h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Source-switched low-energy consumption - green Led witness of charge - For installation on a surface to add the plug-in socket ref. 6612 80 - For recessed installation in false ceiling to add to the framework recessed ref.6612 95 - Terminals of remote control to set at rest - opal Diffuser - Completely recyclable at the end of its useful life

ETIM for 662242 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend LEGRAND / 662242 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.