

INDUSTRIAL COMPONENT DATA

662434 LEGRAND B65LED LVS2 350LM 1H IP65 P/NP

Brand: LEGRAND | Manufacturer Part Number: 662434



Manufacturer	LEGRAND
MPN / Reference	662434
Catalog number	662434
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-61A420BCC1
Generated	2026-07-29

Product Overview

B65LED LVS2 350LM 1H IP65 P/NP

Emergency luminaire B65 - autotest/address maint./non maint. - 350 lm - 1h - LED

B65LED L. VS2 emergency luminaire - 350 lumens - 1h - IP65 - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > WATERTIGHT EMERGENCIES
--------------	----------------------------------

Additional Product Information

Pack (number of units)1

Volume (dm3)2.387

Weight (g)758.00

Product characteristicsAutotest and addressable luminaires - Maintained/Non-maintained (M/NM)

Autotest/addressable luminaires incorporate an automatic self-testing system in order to check emergency lighting

Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective)

Addressable function is activated by setting an ID on each luminaire with configuration tool (Cat.No 0 626 10) and wiring a complementary BUS line

Operating state of all addressable luminaires can be centralized by the control interface (Cat.No 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building's plan on Legrand Vision System (LVS2) PC software Cat.No 0 626 02

These Maintained luminaires can also operate in Non-maintained mode according to the wiring of normal lighting

350 lm - 1h (LEDs)

General characteristicsB65 LED - weatherproof self-contained emergency lighting luminaire LEDWeatherproof LED

maintained and non-maintained units

Certified to IEC and EN 60598-2-22 standards

High power LEDs. IP 65 - IK 07

Plug-in base to ease fixing, cabling and connection

Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours

Charge monitor with a green LED. Power supply: 230 V $\pm$ 10%- 50/60 Hz. Class II

High-capacity screw terminals (2 x 2.5mm²)

3 flexible cable entries for Ø16, 20 and 25 mm tubes

Can be equipped with metallic protection grids Cat.Nos 0 626 90/92

ETIM for 662434 Luminai...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 662434 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.