

INDUSTRIAL COMPONENT DATA**662440 LEGRAND B65LED LVS2 100LM 3H IP55 P/NP**

Brand: LEGRAND | Manufacturer Part Number: 662440



Manufacturer	LEGRAND
MPN / Reference	662440
Catalog number	662440
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-461140C31B
Generated	2026-08-03

Product Overview

B65LED LVS2 100LM 3H IP55 P/NP

B65LED LVS2 Emergency Luminaire - 100 lumens - 3h - IP65 - Permanent/Non-Permanent

B65LED L. VS2 emergency luminaire - 100 lumens - 3h - IP65 - P/NP

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > WATERTIGHT EMERGENCIES****Additional Product Information**

Self-test/centralized LED emergency luminaire (LVS2) - Permanent/Non-permanent (P/NP) - 100 lumens - Autonomy 3 hours - IP65 - LED - Ni-Mh Battery - The luminaire performs a weekly automatic test that checks the status of the lamp and a quarterly automatic test that checks the battery status. - Communicates its status through the LEDs (green and yellow) signaling - For operation in centralized and self-test modes. The centralized mode is activated by giving a code to each luminaire and wiring the emergency to the bus line. Type of mounting Wall extension

function Emergency Lighting/Pathway Identification

Suitable for labelling type Hookable

Type of indicator One side

With pictogram No

Suitable for continuous circuit Yes

With remote switch connection No

With remote control No

Emergency function monitoring system Automatic self-test

Emergency Power Supply System Peripheral unit (single battery)

Battery quality Nimh
Lamp Non-interchangeable LED
With light source Yes
Lamp holder Other
Number of light heads 1
Housing material Plastic
Housing color Grey
Cover material Plastic, opal
Type of voltage AC
Nominal Voltage 230-230 V
Nominal current 43-43 mA
Type of control equipment Current-controlled LED service apparatus
Light distributor Lens/Optics/Diffuser Panel
Assigned service life L70/B50 at 25°C 147000 h
Protection Class (IP) IP65
Impact resistance IK07
Protection class according to IEC 61140 II
Luminaire with limited surface temperature "mark D" according to EN 60598-2-24 No
Lum...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 662440 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.