

INDUSTRIAL COMPONENT DATA

662580 LEGRAND ATEXLED LVS2400LM 1H IP68 P/NP

Brand: LEGRAND | Manufacturer Part Number: 662580



Manufacturer	LEGRAND
MPN / Reference	662580
Catalog number	662580
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-822EF7DE1F
Generated	2026-08-03

Product Overview

ATEXLED LVS2400LM 1H IP68 P/NP

Luminaire emergency ATEXLED LVS2-400 lumens-1h-Permanent/Non-Permanent

Emergency luminaire A TEXLED L. VS2 - 400 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > WATERTIGHT EMERGENCIES

Additional Product Information

Product features

Luminaire emergency LED auto-test / centralized (LVS2) - Permanent / Non-permanent (P/NP) - Explosion-proof - Complies with the atex directive 94/9/EC and standards EN50014-18 and EC 60079-0/1 - Symbol of protection CENELEC/IEC: Ex d IIC (gas), EX tD A21 T80° (powder) - 400 lumens - Autonomy 1 hour - IP66/68 (10m) - Ni-MH battery - The luminaire performs a self-test weekly to check the status of the lamp, and a self-test quarterly to verify the status of the battery. - Communicates its status using the leds (green and yellow) signaling - For operation in modes of centralized and self-test. The centralized mode is active by giving a code to each fixture and wiring the emergency to the bus line. - Installation in surface

General characteristics

ATXLED LVS2 - Luminaires for emergency LED auto-test / centralized watertight - Made according to the standards UNE-EN 60598-2-22 - Luminaires for permanent / non-permanent depending on the wiring done - Flux of 120 lumens in a permanent way - LED with average life on a permanent basis 100,000 hrs - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Source-switched low-energy consumption - green Led witness of load - Terminals of remote control to set at rest - Diffuser transparent - Completely recyclable at the end of its useful life

ETIM for 662580 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sig...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 662580 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.