

INDUSTRIAL COMPONENT DATA

662607PL LEGRAND URA21PLUS LVS2 350LM 1H P/NP

Brand: LEGRAND | Manufacturer Part Number: 662607PL



Manufacturer	LEGRAND
MPN / Reference	662607PL
Catalog number	662607PL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-ECA7E59BF0
Generated	2026-08-04

Product Overview

URA21PLUS LVS2 350LM 1H P/NP

Emergency luminaire URA21LED PLUS LVS2 -350 lumens -1h -Permanent/Non-Permanent

URA21 LED PLUS L. VS2 emergency luminaire - 350 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > NEW URA21 EMERGENCIES / LED
--------------	---------------------------------------

Additional Product Information

Product features

Self-test / centralized LED emergency luminaire (LVS2) - Permanent / Non-permanent (P/NP) - 350 lumens - Autonomy 1 hour - LED - Ni-Mh battery - The luminaire performs a weekly automatic test that checks the condition of the lamp and a quarterly automatic test that checks the battery status. - Communicates its status using LEDs (green and yellow) signalling - For operation in centralized and auto-test modes. Centralized mode is activated by giving a code to each luminaire and cableing the emergency to the bus line

General features

URA21LED PLUS- Self-test / centralized emergency luminaires for indoors - Manufactured according to UNE-EN 60598-2-22 standards - Permanent / non-permanent luminaires depending on the wiring performed - Flow of 100 lumens in permanent mode - LED with half-life of 150,000h - IP 42 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class II - Low power switched source in P/NP models - Green led load indicator - 2x2.5mm² large capacity automatic terminals - Remote control terminals for resting - Surface or recessed installation - 4 cable inputs. 1 open on the back and 3 dephonables of 20mm for hose inlet or rigid tube - Opal diffuser - Fully recyclable at the end of its life

ETIM for 662607PL Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

LED non...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 662607PL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.