

INDUSTRIAL COMPONENT DATA

662633 LEGRAND URAONE LVS2 200LM 1H IP42 P/NP

Brand: LEGRAND | Manufacturer Part Number: 662633



Manufacturer	LEGRAND
MPN / Reference	662633
Catalog number	662633
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-23B3FA5306
Generated	2026-08-02

Product Overview

URAONE LVS2 200LM 1H IP42 P/NP

Emergency luminaire URA ONE - autotest & addressable M/NM - 1h - 200 lm - LED

URA ONE L. VS2 emergency luminaire - 200 lumens - 1h - P/NP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND
--------------	---------

Additional Product Information

Pack (number of units)1

Volume (dm3)1.538

Weight (g)523.00

Product characteristicsAutotest and addressable luminaires - Maintained/Non-maintained (M/NM)

Autotest/addressable luminaires incorporate an automatic self-testing system in order to check the emergency mode

Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective)

Addressable function is activated by setting an ID on each luminaire with infrared configuration tool (Cat.No 0 626 10) and wiring a complementary BUS line

Operating state of all addressable luminaires can be centralized by the control interface (Cat.No 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building's plan on Legrand Vision System (LVS2) PC software (Cat.No 0 626 02)

These Maintained luminaires can also operate in Non-maintained mode according to the wiring of normal lighting
200 lm - 1h (LEDs)

General characteristicsURA ONE - indoor self-contained emergency lighting luminaire LEDLED non-maintained and

maintained units

Certified to IEC and EN 60598-2-22 standards

High power LEDs with optimized lighting distribution

Low consumption switching power supply. Fully recyclable

Plug-in back with pre-cutted holes grid to ease installation and maintenance

Automatic terminals with high capacity: 2 x 2.5mm². IP 42 - IK 07

Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours. Charge monitor with a green LED. Opal diffuser

Power supply: 230 V~ ± 10% - 50/60 Hz. Class II

Flat fl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 662633 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.