

INDUSTRIAL COMPONENT DATA

741431 LEGRAND VN-BASE 2XUSB TIPA 2,4 TO DARK

Brand: LEGRAND | Manufacturer Part Number: 741431



Manufacturer	LEGRAND
MPN / Reference	741431
Catalog number	741431
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-D9D949715C
Generated	2026-08-01

Product Overview

VN-BASE 2XUSB TIPA 2,4 TO DARK

USB charger Valena Next - 2 USB - type A - 2.400 mA - 12 W - dark

Valena Next USB Charger - 2 USB Type A+A - 2400mA - 15W - Dark

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > NEXT VALENA MECHANISMS

Additional Product Information

Product features

Chargers USB - 2 USB - type A - 2.400 mA - 12 W - According to the standard IEC 62684-2011-01 - To quickly reload mobile phones, tablets, smartphones, MP3 and MP4 players. Releases a base - Consumption in passive mode < 0.1 W CLASS II SELV - According to the directive EEC on the harmonisation of the standard load for portable terminals and the reduction of chargers for mobile phones - For installation in flush mounting box minimum depth 40 mm - Allows for connection in shunt with 2P+T - Supplied without cables - Dark General characteristics

Valena Next - USB chargers

ETIM for 741431 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted

Suitable for degree of protection (IP) (EF006755)

IP40

Connection type (EF000124)

Screw terminal

Operating voltage (EF003983)

100 V

Device depth (EF008810)

41 mm

Impact strength (EF004293)

IK04

Anti-bacterial treatment (EF023790)

No

Number of ports USB-C (EF017049)

0

Min. depth of built-in installation box (EF012278)

40 mm

Output voltage (EF003933)

5 V

Power consumption (EF000346)

0.068 W

Device width (EF008808)

74 mm

Device height (EF008809)

74 mm

Colour (EF000007)

Black

Number of ports USB-A (EF000997)

2

RAL-number (EF000116)

9017

Max. output current (EF001315)

3000 mA

Frequency (EF000416)

50 Hz

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 741431 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.