

INDUSTRIAL COMPONENT DATA

741439 LEGRAND VN-CHARGER USBC PD 45W DARK

Brand: LEGRAND | Manufacturer Part Number: 741439



Manufacturer	LEGRAND
MPN / Reference	741439
Catalog number	741439
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-11C0EC9279
Generated	2026-08-01

Product Overview

VN-CHARGER USBC PD 45W DARK

Valena Next USB Charger Base - Type C PowerDelivery - 45W - 2 modules - Dark

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > NEXT VALENA MECHANISMS**

Additional Product Information

Overview

The PowerDelivery Type-C USB charger allows you to power and charge devices such as PCs, tablets, smartphones, etc. description

PowerDelivery USB type C charger that allows faster charging than conventional technologies. They work through an active exchange between the terminal and the charger. 45W - 3000mA. Standby mode consumption: 0.08W CLASS II SELV.

Compliant with the EEC directive on harmonization of charging standard for portable terminals and reduction of chargers for mobile phones. For installation in recessed box with a minimum depth of 40mmspecifications

Model Other

Number of USB-A ports 0

Number of USB-C ports 1

Operating voltage 220-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-20 V

Power consumption 0.074 W

Connection Method Screw-on terminal
Type of mounting Recessed mounted (plaster)
Colour Black
Device width 74 mm
Device height 74 mm
Device Depth 45 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 35 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal Voltage 220-240 V
Power Delivery Yes
Nominal current 0.8-0.8 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 741439 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.