

INDUSTRIAL COMPONENT DATA

741920 LEGRAND VN-CHARGER USB C+C PD 30W BL

Brand: LEGRAND | Manufacturer Part Number: 741920



Manufacturer	LEGRAND
MPN / Reference	741920
Catalog number	741920
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-243C03E4D9
Generated	2026-07-31

Product Overview

VN-CHARGER USB C+C PD 30W BL

Valena Next USB double charger base - Type C+C - 30W - 2 modules - White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > NEXT VALENA MECHANISMS

Additional Product Information

Overview

The USB charger allows two electronic terminals (mobiles, tablets) to be charged simultaneously. It fits perfectly with the Valena Next wiring device.

description

Double USB charger - type C + C - 3,000mA - 30W - To quickly charge mobile phones, tablets, smartphones, MP3 and MP4 players. Consumption in passive mode 0.08 W CLASS II SELV - Complies with the EEC directive on harmonization of the charging standard for portable terminals and the reduction of chargers for mobile phones - For installation in recessed box of minimum depth 40mmspecifications

Model Other

Number of USB-A ports 0

Number of USB-C ports 2

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-20 V

Power consumption 0.063 W
Connection Method Screw-on terminal
Type of mounting Recessed mounted (plaster)
Colour White
Device width 74 mm
Device height 74 mm
Device Depth 45 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 35 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal Voltage 100-240 V
Power Delivery Yes
Nominal current 1-1 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for 741920 Domestic w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 741920 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.