

INDUSTRIAL COMPONENT DATA**864024 LEGRAND NS-BASE USB A+A 3A/5V**

Brand: LEGRAND | Manufacturer Part Number: 864024



Manufacturer	LEGRAND
MPN / Reference	864024
Catalog number	864024
Category	USB power supply
Minimum order	5 Pcs
Document ID	EO-92B6C08FBE
Generated	2026-08-01

Product Overview

NS-BASE USB A+A 3A/5V

Base Dual CHARGER USB A+A Niloé Step - 250 V~

Niloé Step USB Double Charger Base - USB Type A +A

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > NILOÉ MECHANISMS****Additional Product Information****Product features**

Usb A+A dual charger base - 250 V~ - Allow fast charging of mobile phones, tablets, smartphones, MP3, MP4 - Free up space for power bases - Consumption at rest < 0.1 W - Class II MBTS - In accordance with the EEC directive on the harmonization of the standard for recharging portable terminals and the reduction of mobile chargers - Supplied without cable - 5 V - 2.4 A - A equip with front for the base double USB charger or for the dock station with micro USB and trim plate finisher - Built-in or surface mounting - Fastening with screws or claws (included with the mechanism) - Supplied with plastic protector for protection during installation

General features

Niloé Step - USB chargers

ETIM for 864024 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF000124)
Screwed terminal
Operating voltage (EF003983)
100 V
Device depth (EF008810)
41.9 mm
Impact strength (EF004293)
IK04
Anti-bacterial treatment (EF023790)
No
Number of ports USB-C (EF017049)
0
Min. depth of built-in installation box (EF012278)
35 mm
Output voltage (EF003933)
5 V
Power consumption (EF000346)
0.068 W
Device width (EF008808)
75.8 mm
Device height (EF008809)
75.8 mm
Number of ports USB-A (EF000997)
2
Max. output current (EF001315)
3000 mA
Frequency (EF000416)
50 Hz

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 864024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.