

## INDUSTRIAL COMPONENT DATA

## NCO-PRO LEGRAND NETATMO DETECTOR CO SMART

Brand: LEGRAND | Manufacturer Part Number: NCO-PRO



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | LEGRAND                  |
| MPN / Reference | NCO-PRO                  |
| Catalog number  | NCO-PRO                  |
| Category        | Carbon monoxide detector |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-C40E307B2A            |
| Generated       | 2026-07-30               |

## Product Overview

NETATMO DETECTOR CO SMART

Netatmo Smart Carbon Monoxide Detector

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; DOMOTICS MY HOME

## Additional Product Information

In case of carbon monoxide detection: activate the alarm and send a real-time notification to the smartphone. Includes an LED indicator to inform about the status of the device. 85 dB alarm. br/periodic and regular self-tests: br/- carbon monoxide sensor status; br/- battery status; br/- Wi-Fi connection status. br / Possibility to perform the alarm test and deactivate the alarm from the smartphone or on the device itself. Detects carbon monoxide and triggers even if Wi-Fi is not set up (Wi-Fi is required to receive alerts on a smartphone via Netatmo's App Security). Possibility to program monthly, biannual or annual reminders in the App to test the alarm. Low battery notification sent. 2 Integrated CR17450 - 3V batteries, non-replaceable, with a 10-year autonomy. Connectivity: Wi-Fi 802.11 b/g/n (2.4 GHz) - Open/WEP/WPA/WPA-A personal. Bluetooth Low Energy (BLE). The download and configuration of the Security App requires a smartphone or tablet equipped with iOS 10 minimum or Android 5.0 minimum with Bluetooth Low Energy 4.2 (BLE) technology. Compatible with Apple HomeKit. Wall mounting with screws. For indoor use only. Operating temperature: -10°C to 40°C. Dimensions: 100x100mm, depth 23mm. br / Composition: br / - 1 Carbon monoxide detector white finish br / - 1 mounting kit.Independent Yes

Can be connected by cable No

Networkable via radio (standard) Yes

Connectable via radio (optional) No

Maximum number that can be connected to the network 1

Primary power supply Battery...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / NCO-PRO with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.