

INDUSTRIAL COMPONENT DATA

11BG1210A22060 LOVATO THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) 12A, AC COIL 60HZ, 220VAC, 1NO AU..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BG1210A22060



Manufacturer	LOVATO ELECTRIC
MPN / Reference	11BG1210A22060
Catalog number	22060
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-60DEA7F217
Generated	2026-08-01

Product Overview

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 12A, AC COIL 60HZ, 220VAC, 1NO AUXILIARY CONTACT

3P MINICONTACTOR BG12.10A 220V 60HZ

Three-pole contactor, IEC operating current Ie (AC3) = 12A, AC coil 60Hz, 220VAC, 1NO auxiliary contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

11BG1210A22060

Three-pole contactor, IEC operating current Ie (AC3) = 12A, AC coil 60Hz, 220VAC, 1NO auxiliary contact

Technical specifications

Type of product: Contactors Number of poles: 3 Type of coil: AC coil 60Hz Rated coil voltage [V]: 220 IEC operating current Ith (AC1) [A]: 20 IEC operating current and power Ie (AC3) 400V [A/Kw]: 12A / 5.7Kw UL/CSA horsepower ratings 480V [HP]: 7.5 Type of built-in auxiliary contacts: 1NO Type of mounting: Screw / DIN rail 35mm Order code 11BG1210A22060 Weight [g] 186

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 060X045X060

Volume [cm³] 162
Bar code [EAN13] 8013975082362
HS Code 85365080
46.91 £
ETIM for 11BG1210A22060 Low-voltage industrial controls and switchgear (EC000066)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Type of electrical connection of main circuit (EF006819)
Screw connection
Rated control supply voltage AC 60 Hz (EF003979)
220 V
Modular version (EF001126)
No
Rated operation current I_e at AC-4, 400 V (EF008495)
4.8 A
Rated operation current I_e at AC-1, 400 V (EF001393)
20 A
Rated operation current I_e at AC-3, 400 V (EF001392)
12 A
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
1
Number of normally closed contacts as main contact (EF001375)
0
Number of normally open contacts as main contact (EF001374)
3
Rated operation power at AC-3, 400 V (EF001364)
5.7 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BG1210A22060 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.