

INDUSTRIAL COMPONENT DATA

11BGF09T4A04860 LOVATO FOUR-POLE CONTACTOR, AC COIL 60HZ, 48VAC, FASTON TERMINALS

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BGF09T4A04860



Manufacturer	LOVATO ELECTRIC
MPN / Reference	11BGF09T4A04860
Catalog number	04860
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-7A2C171F14
Generated	2026-08-01

Product Overview

FOUR-POLE CONTACTOR, AC COIL 60HZ, 48VAC, FASTON TERMINALS

4P MINICONTACTOR BGF09.T4A 48V 50/60FAS

Four-pole contactor, AC coil 60Hz, 48VAC, Faston terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

11BGF09T4A04860

Four-pole contactor, AC coil 60Hz, 48VAC, Faston terminals

Technical specifications

Type of product: Contactors
Number of poles: 4
Type of coil: AC coil 60Hz
Rated coil voltage [V]: 48
IEC operating current I_{th} (AC1) [A]: 20
IEC operating current and power I_e (AC3) 400V [A/Kw]: 9A / 4.0Kw
UL/CSA horsepower ratings 480V [HP]: 5
Type of mounting: Screw / DIN rail 35mm
Order code 11BGF09T4A04860

Weight [g] 180

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 060X045X060

Volume [cm³] 162

Bar code [EAN13] 8013975121467

HS Code 85365080

ETIM for 11BGF09T4A04860 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC

Type of electrical connection of main circuit (EF006819)

Flat plug-in connection

Rated control supply voltage AC 60 Hz (EF003979)

48 V

Modular version (EF001126)

No

Rated operation current I_e at AC-4, 400 V (EF008495)

4 A

Rated operation current I_e at AC-1, 400 V (EF001393)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

9 A

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of normally closed contacts as main contact (EF001375)

0

Number of normally open contacts as main contact (EF001374)

4

Rated operation power at AC-3, 400 V (EF001364)

4 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BGF09T4A04860 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.