

INDUSTRIAL COMPONENT DATA

11BGP09T4A04860 LOVATO FOUR-POLE CONTACTOR, AC COIL 60HZ, 48VAC, REAR PCB SOLDER PIN

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BGP09T4A04860



Manufacturer	LOVATO ELECTRIC
MPN / Reference	11BGP09T4A04860
Catalog number	04860
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-05F6F54CB7
Generated	2026-08-01

Product Overview

FOUR-POLE CONTACTOR, AC COIL 60HZ, 48VAC, REAR PCB SOLDER PIN

MINICONTACTOR 4P NO 20A AC1 REAR PIN

Four-pole contactor, AC coil 60Hz, 48VAC, rear PCB solder pin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

11BGP09T4A04860

Four-pole contactor, AC coil 60Hz, 48VAC, rear PCB solder pin

Technical specifications

Type of product: Contactors
Number of poles: 4
Type of coil: AC coil 60Hz
Rated coil voltage [V]: 48
IEC operating current I_{th} (AC1) [A]: 20
IEC operating current and power I_e (AC3) 400V [A/Kw]: 9A / 4.0Kw
UL/CSA horsepower ratings 480V [HP]: 5
Type of mounting: Screw / DIN rail 35mm
Order code 11BGP09T4A04860

Weight [g] 186

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 060X045X070

Volume [cm³] 189

Bar code [EAN13] 8013975145234

HS Code 85365080

ETIM for 11BGP09T4A04860 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC

Type of electrical connection of main circuit (EF006819)

PCB connection

Rated control supply voltage AC 60 Hz (EF003979)

48 V

Modular version (EF001126)

No

Rated operation current I_e at AC-4, 400 V (EF008495)

4 A

Rated operation current I_e at AC-1, 400 V (EF001393)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

9 A

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of normally closed contacts as main contact (EF001375)

0

Number of normally open contacts as main contact (EF001374)

4

Rated operation power at AC-3, 400 V (EF001364)

4 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BGP09T4A04860 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.