

INDUSTRIAL COMPONENT DATA

GE0250E LOVATO THREE-POLE CHANGEOVER SWITCH,
250A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GE0250E



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GE0250E
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E9113ED3DF
Generated	2026-07-28

Product Overview

THREE-POLE CHANGEOVER SWITCH, 250A

3P CHANGEOVER SWITCH

Three-pole changeover switch, 250A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GE0250E

Three-pole changeover switch, 250A

Technical specifications

Type of product:Changeover switchesNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:250Type of installation:Screw on plateOrder code GE0250E

Weight [g] 5460

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 245X245X245

Volume [cm³] 14706.125

Bar code [EAN13] 8013975176160

HS Code 85365080

650.96 £

ETIM for GE0250E Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

180 A

Rated permanent current at AC-21, 400 V (EF009165)

250 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (EF007050)

8 kA

Rated operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GE0250E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.