

## INDUSTRIAL COMPONENT DATA

# 11BGP0901A110 BGP0901A110 LOVATO THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) 9A, AC COIL 50/60HZ, 1..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 11BGP0901A110



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LOVATO ELECTRIC               |
| MPN / Reference | 11BGP0901A110                 |
| Catalog number  | BGP0901A110                   |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-3818CAF214                 |
| Generated       | 2026-08-03                    |

## Product Overview

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 9A, AC COIL 50/60HZ, 110VAC, 1NC AUXILIARY CONTACT, REAR PCB SOLDER PIN

Minicont 3P 9A AC3 1NC 110V Printed Circuit

Three-pole contactor, IEC operating current Ie (AC3) = 9A, AC coil 50/60Hz, 110VAC, 1NC auxiliary contact, rear PCB solder pin

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC |
|--------------|---------------------------------------------------------------------------|

## Additional Product Information

11BGP0901A110

Three-pole contactor, IEC operating current Ie (AC3) = 9A, AC coil 50/60Hz, 110VAC, 1NC auxiliary contact, rear PCB solder pin

Technical specifications

Type of product: Contactors  
Number of poles: 3  
Type of coil: AC coil 50/60Hz  
Rated coil voltage [V]: 110  
IEC operating current Ith (AC1) [A]: 20  
IEC operating current and power Ie (AC3) 400V [A/Kw]: 9A / 4.0Kw  
UL/CSA horsepower ratings 480V [HP]: 5  
Type of built-in auxiliary contacts: 1NC  
Type of mounting: Screw / DIN rail 35mm  
Order code 11BGP0901A110  
Weight [g] 200

Qty. per package 1

Multiple qty. of packs per order 1  
Package dimensions [mm] 060X045X070  
Volume [cm<sup>3</sup>] 189  
Bar code [EAN13] 8013975144800  
HS Code 85365080  
49.08 £  
ETIM for 11BGP0901A110 Low-voltage industrial controls and switchgear (EC000066)  
Feature Name  
Feature Value  
Voltage type for actuating (EF008242)  
AC  
Type of electrical connection of main circuit (EF006819)  
PCB connection  
Rated control supply voltage AC 60 Hz (EF003979)  
110 V  
Rated control supply voltage AC 50 Hz (EF003978)  
110 V  
Modular version (EF001126)  
No  
Rated operation current I<sub>e</sub> at AC-4, 400 V (EF008495)  
4 A  
Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393)  
20 A  
Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)  
9 A  
Number of auxiliary contacts as normally closed contact (EF001377)  
1  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of normally closed contacts as main contact (EF001375)  
0  
Number of normally open contacts as main contact (EF001374)  
3  
Rated operation power a...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 11BGP0901A110 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.