

INDUSTRIAL COMPONENT DATA

GA080C LOVATO THREE-POLE SWITCH DISCONNECTOR, DOOR-MOUNT VERSION, 80A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GA080C



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GA080C
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7ABF744CF1
Generated	2026-08-03

Product Overview

THREE-POLE SWITCH DISCONNECTOR, DOOR-MOUNT VERSION, 80A

3P SWITCH 80A-DOOR MOUNTING

Three-pole switch disconnecter, door-mount version, 80A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GA080C

Three-pole switch disconnecter, door-mount version, 80A

Technical specifications

Type of product:Switch disconnectorsNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:80UL Standard:UL98Type of installation:Door-mount versionOrder code GA080C

Weight [g] 406

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 103X079X080

Volume [cm³] 650.96

Bar code [EAN13] 8013975177709

HS Code 85365080

75.14 £

ETIM for GA080C Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Frame clamp

Degree of protection (IP), front side (EF003118)

IP20

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for front mounting 4-hole (EF007247)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

Yes

Rated permanent current at AC-23, 400 V (EF011777)

80 A

Rated permanent current at AC-21, 400 V (EF009165)

80 A

Max. rated operation voltage Ue AC (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GA080C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.